
Chapter 2 Configure A Network Operating System

Chapter 2
Configure A
Network
Operating
System

Downloaded from
api.lacavedespapilles.com
by Maritza & Joseph

INTRODUCTION: UNLOCKING THE POWER OF YOUR NETWORK

Imagine building a house without a blueprint or a car without an engine. In the world of networking, the "engine" that brings your hardware to life is a **Network Operating System (NOS)**. This specialized software is the brain of your routers and switches, managing all traffic,

enforcing security policies, and ensuring connectivity. **Chapter 2 Configure A Network Operating System** is often the first real, hands-on step for any aspiring network administrator. It moves beyond theory and into the terminal, where you transform a blank piece of hardware into a functioning part of a global communication system. This guide will walk you through every critical aspect of this process, from initial access to saving your final configuration,

ensuring you build a solid foundation for your entire network infrastructure.

WHAT IS A NETWORK OPERATING SYSTEM (NOS)?

Before diving into commands, it is essential to understand what you are actually configuring. A Network Operating System is the software that controls all functions on a network device. Unlike a desktop OS like Windows or macOS, a NOS is highly specialized for tasks like packet forwarding, routing protocol calculations, and managing network interfaces.

Common Types of Network Operating Systems

While the principles in **Chapter 2 Configure A Network Operating System** apply broadly, the specific commands often vary by vendor. The most widely used family is Cisco's Internetwork Operating System (IOS), which has evolved into IOS-XE and NX-OS for data centers. Other significant players include Juniper's Junos OS and open-source options like VyOS and FRRouting. Most entry-level courses focus on

Cisco IOS, which provides the foundational language for network configuration.

METHODS OF ACCESS: GETTING INTO THE SYSTEM

You cannot configure what you cannot access. **Chapter 2 Configure A Network Operating System** typically begins by establishing a connection to the device. There are several methods to do this, each suited for different stages of deployment.

Console Access: The Out-

of-Band Connection

This is the most fundamental method, especially for initial configuration. You physically connect a computer to the device's console port using a rollover cable and a serial-to-USB adapter. You then use terminal emulation software (like PuTTY, Tera Term, or SecureCRT) to establish a session. Console access is secure because it does not rely on the network being operational, making it ideal for troubleshooting and setting up the device for the first time.

UNDERSTANDING

Remote Access: Telnet and SSH

Once the device has an IP address and basic connectivity, you can access it remotely.

Telnet is the older protocol, but it transmits

data—including passwords—in plain text, making it a security risk. **Secure**

Shell (SSH) is the modern standard, encrypting the entire session. Configuring

VTY (Virtual Teletype) lines for secure remote access is a core task in

Chapter 2 Configure A Network Operating System.

THE COMMAND- LINE INTERFACE (CLI) MODES

Working with a network operating system is almost exclusively done through a text-based Command-Line Interface (CLI). The CLI is hierarchical, meaning you must be in the correct "mode" to execute specific commands.

Understanding this structure is critical to avoiding syntax errors and unintended changes.

User EXEC Mode

This is the first mode you encounter after accessing the device. It

is heavily restricted, allowing only basic monitoring commands like `ping`, `traceroute`, and `show`. The prompt typically ends with a `>` symbol (e.g., `Router>`). You cannot make configuration changes here.

Privileged EXEC Mode

Often called "enable mode," this is the operational hub. You enter it by typing the `enable` command and providing the appropriate password. The prompt changes to a `#` symbol (e.g., `Router#`). From here, you can view detailed system information, run diagnostic tools,

and execute commands that affect the device's current state. However, direct configuration changes are still not possible here.

Global Configuration Mode

This is where the real work begins. From Privileged EXEC mode, you type `configure terminal` (or often just `conf t`). The prompt changes to include `(config)` (e.g., `Router(config)#`). Global configuration commands affect the entire device, such as setting the hostname, enabling routing protocols, or creating user accounts.

Subconfiguration Modes

Once in Global Configuration mode, you can drill down into specific sub-modes to configure specific components. These include:

- **Interface Configuration**
Mode: (e.g., Router(config-if)#) Used to set IP addresses, speed, and duplex settings on a specific port.
- **Line Configuration**
Mode: (e.g., Router(config-line)#) Used to configure console, AUX,

and VTY lines for access control.

- **Router Configuration**
Mode: (e.g., Router(config-router)#) Used to configure dynamic routing protocols like OSPF or EIGRP.

STEP-BY-STEP: PERFORMING A BASIC CONFIGURATION

Now that you understand the landscape, let's apply the knowledge from **Chapter 2 Configure A Network Operating System** with a practical setup. We will assume you have console access and are at the User EXEC mode prompt.

Step 1: Enter Privileged and Global Configura tion Modes

1. **Router> enable**
(Enter this command to go to Privileged EXEC mode)
2. **Router# configure terminal** (Enter this to reach Global Configuration mode)
3. **Router(config)**

(You should now see the prompt indicating you are in the correct mode.)

Step 2: Set the Device Hostnam e

Identifying your devices is vital for management. The hostname appears prominently in the CLI prompt.

**Router(config)#
hostname Branch-Office-SW1**

The prompt will immediately change to Branch-Office-SW1(config)#. This

confirms the change is active.

Step 3: Secure Access with Password S

Security is non-negotiable. You must protect access to the different modes.

- **Secure Enable Access:**

- Branch-Office-SW1(config)# **enable secret MySecure Password**
- *Note:* Use enable

secret over enable password. The former is encrypted, while the latter is stored in plain text.

- **Secure the Console Line:**

- Branch-Office-SW1(config)# **line console 0**
- Branch-Office-SW1(config-line)# **password ConsoleP**
- Branch-Office-SW1(config-line)# **login**
- Branch-Office-

- ```
SW1(config
-line)#
exit
```
- **Secure VTY Lines (for remote SSH/Telnet):**
    - Branch-Office-SW1(config)# **line vty 0 4** (This selects the first five virtual lines)
    - Branch-Office-SW1(config-line)# **password VtyPass**
    - Branch-Office-SW1(config-line)# **login**
    - Branch-Office-SW1(config-line)# **transport**

```
input ssh
(This
restricts
access to
only the
secure SSH
protocol)
◦ Branch-Office-SW1(config-line)#
exit
```

## Step 4: Configure an Interface (SVI or Physical)

For a switch, you often configure a Switch Virtual Interface (SVI) for management. For a router, you configure a

physical  
GigabitEthernet  
interface.

- **Switch**

**Example (VLAN  
1 Management  
Interface):**

- Branch-Office-SW1(config)#  
**interface  
vlan 1**
- Branch-Office-SW1(config-if)# **ip  
address  
192.168.1  
.10  
255.255.2  
55.0**
- Branch-Office-SW1(config-if)# **no  
shutdown**  
(This is a  
crucial  
command  
to activate  
the

interface)

- Branch-Office-SW1(config-if)# **exit**

- **Router**

**Example:**

- Branch-Office-R1(config)#  
**interface  
gigabitethernet  
0/0**
- Branch-Office-R1(config-if)# **ip  
address  
10.0.0.1  
255.255.2  
55.252**
- Branch-Office-R1(config-if)#  
**description  
Link to  
Main  
Office**  
(Adding a

description helps with documentation)

- Branch-Office-R1(config-if)# **no shutdown**

## Step 5: Set a Banner (Legal Notice)

Configuring a Message of the Day (MOTD) banner provides a legal warning before anyone accesses the system.

```
Branch-Office-SW1(config)#
banner motd $
Authorized Access
Only. All Activities
```

### **are Monitored. \$**

The "\$" character is the delimiter. Whatever you type between the delimiters will appear as the banner message.

---

## **MANAGING THE CONFIGURATION FILES**

---

A fundamental concept in **Chapter 2 Configure A Network Operating System** is the difference between running-config and startup-config. Understanding these is key to ensuring your changes persist.

## The Running Configura

# tion

This is the configuration currently active in the device's memory (RAM). Any command you type immediately takes effect in the running-config. However, if the device loses power or reboots, all changes in the running-config are lost unless saved.

## The Startup Configuration

This file is stored in Non-Volatile RAM (NVRAM). It contains the configuration that the device loads when it boots up. To make your changes

permanent, you must copy the running-config to the startup-config.

**Branch-Office-SW1#  
copy running-config  
startup-config**

Alternatively, you can use the abbreviated command: `write memory` or `wr`.

---

### VERIFICATION: USING THE "SHOW" COMMANDS

---

Configuration is only half the battle. You must verify that your commands were applied correctly and that the system is functioning as intended. The `show` command is your most powerful diagnostic tool.

1. **show running-config:** Displays the current

active  
configuration.  
This is the most

common  
verification  
command.